


Accessories for duct washing machines



Brushes

Pressovac offers a large selection of high quality brushes of different forms, sizes, and bristle materials.

The brushes should be selected according to brushing equipment, duct size, amount and structure of the grease build-up in the duct. Brushes with hard bristles are appropriate for foaming operation. When the duct has large amount of thick grease residue, extra hard bristles are recommended. In cases when the grease is strongly solidified, we recommend a moderate use of brushes with carbide or stainless steel bristles to help the chemical solution to penetrate the grease layer.



Brush type	S-brush	L-brush	C-brush
Compatible machines	PDW-25 / PDW-30 PDW-40	PDW-25 / PDW-30 PDW-40	EDW-15/EDW-15S Combi-shaft
Compatible ducts	rectangular and round ducts with multiple bends Ø200-800mm	rectangular and round ducts Ø150-500mm	rectangular and round ducts Ø125-315mm
Brushing segment	40mm	150mm	20mm
Bristle types	Hard / Extra Hard Carbide / Stainless Steel	Hard / Extra Hard Carbide / Stainless Steel	Hard / Extra Hard Carbide / Stainless Steel
Brush size (mm)	Ø200 Ø250 Ø250 Ø400 Ø500 Ø630 Ø800	Ø200 Ø250 Ø250 Ø400 Ø500	Ø125 Ø160 Ø200 Ø250 Ø315
Brush sets	7pcs, Ø200-800mm	5pcs, Ø200-500mm	5pcs, Ø125-315mm



Grease plates

Grease plates with 5x1m extension rods for removing grease from grease ducts.



Carrying bag for shafts

Long-lasting, heavy duty carrying bag for shafts and brushing accessories.

Air compressor K-370 for pneumatic brushing machines


Durable, high efficiency compressor to power pneumatic duct washing machines PDW.



Technical Specifications	K-370
Air output	370l/min
Maximum pressure	10 bar
Pressure tank	30L
Engine power	2,2kW
Power supply	1 phase, 230V, 50Hz, 10A
Noize level	66dB
Dimensions (LxHxW)	87x59x56cm
Weight	86kg

- High air output
- Solid frame
- 30L pressure tank included
- Optimal for lengthy cleaning operations
- Compact, easy to manoeuvre and transport





Accessories for duct washing machines

Foam tank

Foamer with a 24L stainless steel pressurizable tank to create and spread the foam via high-pressure hose integrated in PDW/EDW/CS.



Foaming Agent X1

Strong alkaline and high foaming agent ideal for foam-washing grease ducts and stainless steel surfaces.



Foaming nozzle

High quality high pressure foaming nozzles built with 1/4" male quick connect. To be used for foaming in PDW, EDW and CS when using high-pressure washer




Rinsing nozzles

Rinsing nozzles built with 1/4" male quick connect nipples and available with multiple spray angles. To be used in PDW, EDW and CS.



Nozzle	Spray angle	Spray heads
green	25°	1
white	40°	1
T-shape	65°	2

Accessories for duct washing machines HW-45T HotWasher



HW-45T is a high pressure electric boiler with 45L internal water tank. With a maximum pressure of 140 bar and heat exchange of +45°C, this is the ideal high-pressure boiler to generate hot water for the rinsing phase. Can be used in enclosed areas as a source of pressurized hot water.



- stainless steel patented boilers
- Continuous water heating at constant temperature
- 45 liters internal water tank and direct connection to water supply
- Pressure up to 150 bar
- Automatic shutoff technology "Total stop"
- Stainless steel frame and panels

Technical Specifications	HW-45T
Maximum pressure	140 bar
Flow rate	5,5L/min
Heat exchange	+45°C
Maximum temperature	+90°C
Power	16,5kW
Power supply	3 phase, 400V, 24A, 50Hz
Water tank	45L
Frame structure	stainless steel
Dimension (LxHxW)	95x80x61cm
Weight	76kg
Accessories included	10 mt hose - spray gun - lance - nozzle - quick connect screw type couplers - stainless steel injector

